

The New Cambridge Interactive Whiteboard from Hitachi

Simple to operate and the best screen resolution available



The New Cambridge Board is simple to operate, very durable and can be used as an ordinary whiteboard if a power cut occurs or a supply teacher is covering. The Cambridge Board provides the highest resolution available and works faster than most people can write!

- Robust surface.
- Can be used as an ordinary whiteboard.
- Fast and very accurate.
- Re-chargeable pen holder with two slim line re-chargeable pens.
- New function buttons for most common functions at the touch of a pen.
- Five year warranty.
- Able to be powered through USB cable - no power supply required.
- Bluetooth enabled.
- Available in 77" and 60".
- RoHS approved.
- Can be resurfaced at a fraction of the cost of a new board.



HITACHI
Inspire the Next

The New Cambridge Interactive Whiteboard from Hitachi

Simple to operate and the best screen resolution available

Every new Cambridge Board includes the most advanced presentation software available - the StarBoard Software Version 7.0. Easy to learn and install, it is feature-rich, fully customisable and designed to help the user become confident with the whiteboard within minutes. The intuitive toolbar design and natural feel of the pen makes the new Cambridge Board a joy to use.



Item	Specification	
Product name	Cambridge Board 77.5"	Cambridge Board 60"
Model No.	HTCB-77G	HTCB-60G
Input methods	Electromagnetic	
Interface to computer	Serial (RS-232C) and USB	
Effective screen size	77.5 inches (diagonal)	60 inches (diagonal)
Dimensions (mm)	1,727 (W) x 1,327 (H) x 49 (D)	1,372 (W) x 1,060 (H) x 49 (D)
Sampling rate	Approximately 3,000mm/s	
Accuracy	±1.0 mm	
Input Voltage/Current	9VDC/1.7A	
Weight	24 kg	16.3 kg
Bundled software	StarBoard Software, 1 set	
Environmental conditions	Ambient temperature 5-46°C Humidity 20-80%	
Battery life	Continuous operating time approximately 40hours ¹	
Software required	Starboard Software 7.0 or newer version	

¹ The battery life varies according to the temperature and the usage environment. The life time of full recharging is approximately 500 times.

Further information:

Hitachi Software Engineering (UK) Limited

10 Old Bailey
London EC4M 7NG United Kingdom
Tel: +44 (0)20 7038 1030
Fax: +44 (0)20 7038 1130

Email : sales@hitachi-software.co.uk

Hitachi Software Engineering France S.A.S

7th Floor, 64 rue du Dessous des Berges
75013 Paris, France
Tel: +33 (0) 153 827 600
Fax: +33 (0) 153 827 619

Email : starboard@hitachisoft-eu.com

Hitachi Software Engineering Europe A.G.

Neues Kranzler Eck, Kurfürstendamm 22
D-10719 Berlin, Germany
Tel : +49 (0)30 8877 2600
Fax : +49 (0)30 8877 2610

Email : starboard@hitachisoft.de

HITACHI
Inspire the Next

www.hitachi-education.com